



LM
Lower mount



UC
U-Clamp

GAUGES - LIQUID

4" X 1/4" MOUNT -
SS CASE / SS INTERNALS

FEATURES & APPLICATIONS:

- Used in hydraulic and pneumatic systems, compressors, regulator machine, and suitable for fluid medium or gaseous which does not clog connection port or corrode stainless steel. Can use for severe service conditions where pulsation or vibration exist. Premium quality and long life.

Case Venting: Liquid filled gauges should be vented to atmosphere to relief internal case pressure prior to use. You can easily do this by turning the valve lever on the back of the gauge to the open position. Liquid-Fill gauges are typically shipped with the valve in the closed position.

TECHNICAL DATA:

- **CASE:** Stainless Steel 316 SS
- **WINDOW:** Glass
- **INTERNAL:** Stainless Steel 304 SS
- **CONNECTION:** Stainless Steel 316 SS
- **ACCURACY:** $\pm 1.0\%$ of span
- **TEMPERATURE RANGE:** -4°F to 140°F

ALL STAINLESS STEEL

Face Size	Mount	PSI	Part #	Part #
4"	1/4" NPT		LM	UC
		15 psi / 103 kpa	G40151PSS	G40152PSSU
		30 psi / 200 kpa	G40301PSS	G40302PSSU
		60 psi / 400 kpa	G40601PSS	G40602PSSU
		100 psi / 700 kpa	G401001PSS	G401002PSSU
		160 psi / 1,100 kpa	G401601PSS	G401602PSSU
		200psi / 1,400 kpa	G402001PSS	G402002PSSU
		300 psi / 2,100 kpa	G403001PSS	G403002PSSU
		400 psi / 2,800 kpa	G404001PSS	G404002PSSU
		600 psi / 4,000 kpa	G406001PSS	G406002PSSU
		1,000 psi / 7,000 kpa	G4010001PSS	G4010002PSSU
		1,500 psi / 10,000 kpa	G4015001PSS	G4015002PSSU
		2,000 psi / 14,000 kpa	G4020001PSS	G4020002PSSU
		3,000 psi / 21,000 kpa	G4030001PSS	G4030002PSSU
		5,000 psi / 35,000 kpa	G4050001PSS	G4050002PSSU
		10,000 psi / 70,000 kpa	G40100001PSS	G40100002PSSU
		15,000 psi / 103,421kpa	G40150001PSS	G40150002PSSU



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.