



SEALFAST
THE SIMPLE SOLUTION

GAUGES



LM

Lower mount

GAUGES HD - LIQUID

6" X 1/2" MOUNT -
STEEL CASE / SS INTERNALS

FEATURES & APPLICATIONS:

- Used in hydraulic and pneumatic systems, compressors, regulator machine, and suitable for fluid medium or gaseous which does not clog connection port or corrode stainless steel. Can use for severe service conditions where pulsation or vibration exist. Premium quality and long life.

Case Venting: Liquid filled gauges should be vented to atmosphere to relief internal case pressure prior to use. You can easily do this by turning the valve lever on the back of the gauge to the open position. Liquid-Fill gauges are typically shipped with the valve in the closed position.

TECHNICAL DATA:

- **CASE:** Stainless Steel 304 SS
- **WINDOW:** Glass
- **INTERNAL:** Stainless Steel 304 SS
- **CONNECTION:** Stainless Steel 316 SS
- **ACCURACY:** $\pm 1.0\%$ of full scale
- **TEMPERATURE RANGE:** -4°F to 140°F

ALL STAINLESS STEEL

Face Size	Mount	PSI	Part #
6"	1/2" NPT		LM
		30 psi / 200 kpa	118AL60N4P30
		60 psi / 400 kpa	118AL60N4P60
		100 psi / 700 kpa	118AL60N4P100
		160 psi / 1,100 kpa	118AL60N4P160
		200psi / 1,400 kpa	118AL60N4P200
		300 psi / 2,100 kpa	118AL60N4P300
		400 psi / 2,200 kpa	118AL60N4P400
		600 psi / 4,000 kpa	118AL60N4P600
		1,000 psi / 7,000 kpa	118AL60N4P1000
		1,500 psi / 10,000 kpa	118AL60N4P1500
		2,000 psi / 14,000 kpa	118AL60N4P2000
		3,000 psi / 21,000 kpa	118AL60N4P3000
		5,000 psi / 35,000 kpa	118AL60N4P5000
		10,000 psi / 70,00 kpa	118AL60N4P10000



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.