



SEALFAST
THE SIMPLE SOLUTION

HOSES
FIRE



FIRE

FIRE - SINGLE JACKET

EPDM LINED - 500# Test

FEATURES & APPLICATIONS:

- This hose is 100% polyester with a outer yellow polymeric coating having high ozone and abrasion resistance. A wide range of applications including power plants, steel plants, mines and all other types of industry needing high visibility and maintenance free hose. Recommended 225 psi working pressure.



TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** n/a
- **Tube:** EPDM
- **Cover:** Red Polymeric Coating
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Maximum advised operating/working pressure that should not exceed 90% of Service Test Pressure (Stenciled on hose)

RED POLYMERIC COATING / POLYESTER-EPDM LINED

| ID | OD | Length | Working Pressure | Service Test Pressure | Bend Radius | Lbs per Roll | Bowl Size | Part # |
|--------|-----|----------|------------------|-----------------------|-------------|--------------|-----------|-------------------------------|
| 1-1/2" | n/a | 50'/100' | 135 | 250 | n/a | 11/21 | 1-3/4" | NOVADURA150 / NOVADURA150 100 |
| 2-1/2" | n/a | 50'/100' | 135 | 250 | n/a | 20/39 | 2-13/16" | NOVADURA250 / NOVADURA250 100 |



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.