



FIRE

FIRE - SINGLE JACKET

EPDM LINED - 500# Test

FEATURES & APPLICATIONS:

- This hose is 100% polyester with a outer yellow polymeric coating having high ozone and abrasion resistance. A wide range of applications including power plants, steel plants, mines and all other types of industry needing high visibility and maintenance free hose. Recommended 225 psi working pressure.



TECHNICAL DATA:

- **Temp Range:** -22° F to +158° F
- **Cover:** Yellow Polymeric Coating
- **Tube:** EPDM
- **Safety Factor:** n/a
- **Branding:**

NOTES:

- Maximum advised operating/working pressure that should not exceed 90% of Service Test Pressure (Stenciled on hose)

YELLOW POLYMERIC COATING / POLYESTER-EPDM LINED

ID	OD	Length	Working Pressure	Service Test Pressure	Bend Radius	Lbs per Roll	Bowl Size	Part #
1-1/2"	n/a	50'/100'	135	250	n/a	11/21	1-3/4"	NOVADURA150Y / NOVADURA150Y 100
2-1/2"	n/a	50'/100'	135	250	n/a	20/39	2-13/16"	NOVADURA250Y / NOVADURA250Y 100



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.