



WATER YELLOW JACKET HEAVY DUTY DISCHARGE

FEATURES & APPLICATIONS:

• Designed for heavy duty water discharge applications in agriculture, construction, industry & mining. Abrasion resistant PVC cover & PVC tube provide long service life.

> • Attains higher working pressure from a synthetic woven polyester reinforcement.

> > • At 120°F the working pressure will be reduced to .40% of the working pressure at 70 °F

> > > • Rubber like hose

TECHNICAL DATA:

- **Temp Range:** -36° F to +178° F
- Cover: Yellow PVC/NBR
- Tube: PVC/NBR
- Reinforcement: 2 spiral plies & 1 longitudinal ply
- Safety Factor: 3:1 min
- Branding:

YELLOW PVC/NBR								
ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Vacuum Rating "HG"	Part #
1-1/2"	0.11″	300′	200	600	n/a	0.32	n/a	W200-150
2"	0.11″	300′	200	600	n/a	0.40	n/a	W200-200
2-1/2"	0.12″	300′	200	600	n/a	0.59	n/a	W200-250
3"	0.12″	300′	200	600	n/a	0.70	n/a	W200-300
4"	0.13″	300′	200	600	n/a	0.87	n/a	W200-400
6"	0.15″	300′	200	600	n/a	1.50	n/a	W200-600
8"	0.17″	300′	200	600	n/a	2.40	n/a	W200-800
Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.								

sales@Seal Fast.com

800.231.0734

Seal Fast.com

603 Harvey Wilson Drive, Houston, TX 77020