



**GODZILLA 10**  
NITRILE 10



**FEATURES & APPLICATIONS:**

- Designed for the delivery of fluids, resistant to many products such as oil, grease, acids, bases, salts, sewage & seawater.
- Irrigation - Agriculture - Pump Discharge  
- Industrial Wash Down
- Through the Weave Technology
- Less weight than Rubber Discharge
- 70% PVC / 30% NBR

**TECHNICAL DATA:**

- **Temp Range:** -4° F to +176° F
- **Cover:** Ribbed, highly resistant to oil, abrasion and weathering
- **Tube:** Nitrile-PVC oil/weather resistant rubber, polyester reinforcement
- **Reinforcement:** n/a
- **Safety Factor:** 3:1 min
- **Branding:**

**BLACK NITRILE 10**

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Vacuum Rating "HG"	Part #
1-1/2"	.08"	200'	200	150	n/a	.21	n/a	Nitrile 10150TW
2"	.08"	200'	200	150	n/a	.32	n/a	Nitrile 10200TW
2-1/2"	.08"	200'	200	150	n/a	.44	n/a	Nitrile 10250TW
3"	.10"	200'	200	150	n/a	.48	n/a	Nitrile 10300TW
4"	.10"	200'	200	150	n/a	.66	n/a	Nitrile 10400TW
6"	.12"	200'	200	150	n/a	1.14	n/a	Nitrile 10600TW
8"	.12"	100'	200	150	n/a	1.54	n/a	Nitrile 10800TW
10"	.14"	100'	200	150	n/a	2.05	n/a	Nitrile 101000TW
12"	.14"	100'	200	150	n/a	2.05	n/a	Nitrile 101200TW



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.