



PETROLEUM

TANK TRUCK -
300 PSI

FEATURES & APPLICATIONS:

- Designed for transferring gasolines & petroleum products
- Excellent for suction & discharge of seawater, oil based mud, & other general purpose uses.
- Suitable for up to 50% aromatics.



TECHNICAL DATA:

- **Temp Range:** -22° F to +212° F
- **Cover:** Black, CR/Nitrile
- **Tube:** Nitrile Rubber
- **Reinforcement:** High tensile textile fabric; steel wire helix; anti-static copper wire
- **Safety Factor:** 3:1 min
- **Branding:**



BLACK NITRILE BLEND / NITRILE

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per ft.	Part #
1-1/2"	2.01"	100'	300	900	6"	.94	TT 150-2 100
2"	2.56"	100'	300	900	8"	1.41	TT 200-2 100
3"	3.70"	100'	300	900	12"	2.42	TT 300-2 100
4"	4.76"	100'	300	900	16"	3.36	TT 400-2 100
6"	6.89"	20'	300	900	24"	6.72	TT 600-2 20

Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.