



SEALFAST
THE SIMPLE SOLUTION

HOSES
HYDRAULIC



HYDRAULIC

HYDRAULIC 4SH

FOUR SPIRAL STEEL WIRE
REINFORCED 100R13 -
(heavy duty-high impulse)

FEATURES & APPLICATIONS:

- The hose is suitable for use with:
Hydraulic fluids in accordance with
ISO 6743-A64 with the exception of
HFD R, HFD S & HFD T at temperatures
ranging from -20°F to 212°F
- The hoses are not suitable for use with
castor oil based on ester based fluids.
Meets or exceeds EN856-4SH



TECHNICAL DATA:

- **Temp Range:** -20° F to +212° F
- **Cover:** Oil & Weather Resistant Synthetic Rubber
- **Tube:** Oil & Weather Resistant Synthetic Rubber
- **Reinforcement:** 4 spiral plys of Steel Wire wrapping in alternating directions.
- **Safety Factor:** 4:1 min
- **Branding:** Size 4SH DIN EN 856 4700PSI W.P. fxs

OIL RESISTANT SYNTHETIC RUBBER

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	Lbs per Roll	Vacuum Rating "HG"	Part #
3/4"	1.3"	100' +/-	6000	24000	114"	11"	---	4SH-12
1"	1.57"	100' +/-	5500	22000	144"	13"	---	4SH-16
1-1/4"	1.85"	100' +/-	4700	18000	171"	18"	---	4SH-20
1-1/2"	2.17"	100' +/-	4200	16000	230"	22"	---	4SH-24
2"	2.74"	100' +/-	3600	14000	331"	27"	---	4SH-32



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.